

OP5650 Specifications

Product name	OP5650 V3
Power rating	Input: 100-240VAC, 50-60Hz, 8A-4A Power: 600W
Input/output power	-30V to +30V maximum
I/O connectors	4 panels of 4 DB37F connectors 4 rear SFP ports
Monitoring connectors	4 panels of RJ45 connectors
PC interface	Standard PC connectors (monitor, keyboard, mouse and network)
PCI slots	3 PCIe slots (capable of accommodating up to 2 PCI boards)
Hard disk	512 Gb SSD
Dimensions	48.3 x 45.7 x 17.8cm (19" x 18" x 7")
Weight	With PC: 9.07 - 15 Kg (20 lbs to 33 lbs) Without PC: 4.54 - 5.9 Kg (10 lbs to 13 lbs)
Operating temperature	10 to 35 °C (50 to 95°F)
Storage temperature	-55 to 85°C (-67 to 185°F)
Maximum rated ambient temperature	40C° (104°F)
Relative humidity	10 to 90% non-condensing
Maximum altitude	2000 m (6562 ft.)

Environmental

Intended use	For Indoor use only
Ventilation requirements	Do not block vents on the unit. Allow sufficient ventilation space around the unit (recommended 6" at sides and rear) when not mounted in a standard rack.
Operating temperature	10 to 40 °C (50 to 104°F)
Storage temperature	-55 to 85°C (-67 to 185°F)
Relative humidity	10 to 90% non-condensing
Maximum altitude	2000 m (6562 ft.)
Pollution	Degree 2