


# OP5969-1 RS422 Digital Inputs and Outputs (DIO)



The OP5969-1 is an I/O expansion option available for the OP4510, OP4512, and OP4610XG simulators and also for the OP4520 I/O expansion unit. The I/O Expansion connects to the rear-interface of the simulator and provides **4x DB9 connectors** containing **6 TX** and **6 RX** for **RS422 signals**. These signals are typically used to transmit differential encoder inputs and outputs.

- [General Pin Assignments](#)
- [Specifications](#)
  - [RS422 Digital In](#)
  - [RS422 Digital Out](#)

## General Pin Assignments

| DB9F<br>Pin | RS422 OUT CH<br>00-02 | DB9F<br>Pin | RS422 IN CH00-<br>02 |   |               | DB<br>9F<br>Pin | RS422 OUT<br>CH 03-05 | DB<br>9F<br>Pin | RS422 IN<br>CH03-05 |
|-------------|-----------------------|-------------|----------------------|---|---------------|-----------------|-----------------------|-----------------|---------------------|
| 1           | TX0+                  | 1           | RX0+                 |   |               | 1               | TX3+                  | 1               | RX3+                |
| 2           | TX1+                  | 2           | RX1+                 | 2 | TX4+          | 2               | RX4+                  |                 |                     |
| 3           | TX2+                  | 3           | RX2+                 | 3 | TX5+          | 3               | RX5+                  |                 |                     |
| 4           | N.C                   | 4           | N.C                  | 4 | N.C           | 4               | N.C                   |                 |                     |
| 5           | +12V limited*         | 5           | +12V limited*        | 5 | +12V limited* | 5               | +12V limited*         |                 |                     |
| 6           | TX0-                  | 6           | RX0-                 | 6 | TX3-          | 6               | RX3-                  |                 |                     |
| 7           | TX1-                  | 7           | RX1-                 | 7 | TX4-          | 7               | RX4-                  |                 |                     |
| 8           | TX2-                  | 8           | RX2-                 | 8 | TX5-          | 8               | RX5-                  |                 |                     |
| 9           | DGND                  | 9           | DGND                 | 9 | DGND          | 9               | DGND                  |                 |                     |

\*Same 12V for all the connectors. 400mA total

## Specifications

### RS422 Digital In

|                            |                       |
|----------------------------|-----------------------|
| <b>Number of channels</b>  | 6 differential inputs |
| <b>Detection threshold</b> | ± 0.5 V               |
| <b>Input current</b>       | ± 3 mA                |
| <b>Delay Low-to-High</b>   | 65 ns                 |

### RS422 Digital Out

|                               |                        |
|-------------------------------|------------------------|
| <b>Number of channels</b>     | 6 differential outputs |
| <b>High level (With load)</b> | 2.5 V min @ -20 mA     |
| <b>Low level (With load)</b>  | 0.5 V max @ 20 mA      |
| <b>Delay Low-to-High</b>      | 55 ns                  |